



Control4® 7" Portable Touch Screen with Camera

Control4® 7" Portable Touch Screen with Camera C4-TSMC7-EN-BL (Black)
Control4® 7" Portable Touch Screen with Camera International C4-TSMC7-INT*

The Control4® 7" Portable Touch Screen with Camera delivers always-on, dedicated system control in a sleek tablet form-factor that works as a portable or a tabletop touch screen for ultimate control and flexibility. The 7" Portable Touch Screen with Camera features full-motion video intercom and the fidelity of wideband audio intercom for crystal-clear communications and control throughout a home or business. Intercom is optional and may be activated with the purchase of an Intercom License (C4-Intercom-E).

- Easily configured as a true portable or as a tethered tabletop for flexible installation.
- Integrated camera with full-motion video for high-quality video communications with a Door Station and 7" In-Wall Touch Screen with Camera.
- Integrated speakers and dual microphones with beam forming and G.722 wideband audio for uncompromised high-fidelity sound.
- Audio intercom integration with the following in-wall touch screens: 5" In-Wall Touch Screen (C4-TSWMC5-EG-XX) or 7" In-Wall Touch Screen (C4-TSWMC7-EG-XX).
- Full-color, capacitive LCD touch screen control along with 4 hard programmable buttons offers convenient fingertip control.
- Wired and wireless connections through Wireless-N and 10/100 BaseT Ethernet.
- Flexible power options with AC power supply adapter, Power over Ethernet (PoE) or internal battery.



*Includes power supply adapters for UK, EU, AU

Control4™

Control4® 7" Portable Touch Screen with Camera

Model Number	C4-TSMC7-EN-BL (Black)
Display	
Camera	640 x 480 VGA 30 fps Min. lamination: 5 Lux Viewing angle: 60 degrees
Display dimensions	7-inch TFT 800 x 480 pixels
Touch screen	Capacitive touch
Programmable buttons	4
Intercom	
Microphone	Dual microphones Voice pickup from 10' (3.048m) away Beam forming
Speaker	Internal
Video and audio	Full duplex video (H.264) and audio (G.722)
Network	
WiFi	Wireless-N (2.4GHz 802.11n/g) RF frequency: 2.4GHz Antenna: Internal Encryption: 64/128 WEP, TKIP/AES Authentication: WPS, WEP, WPA, WPA2
Ethernet	10/100 Base-T Ethernet RJ-45
Power	
Power supply	PoE (IEEE802.3af) AC 100V - 240V, 50-60Hz
Battery	Suspend: 20 hours Typical use: (default setting) 12 hours Charge time: 6 hours
Other	
Reset	2 operation modes: Press once to reboot system or press and hold to restore to its factory default settings
Operating temperature	32° F - 104° F (0° C - 40° C) 95% non-condensing
Storage temperature	-4° F - 113° F (-20° C - 45° C)
Mounting Options	
Dimensions (W x H x D)	5" (127 mm) x 7.5" (190.5 mm) x 0.75" (19.05 mm) not including charging dock
Mounting	Portable or Tabletop
Weight	1.75 lbs (.793 kg)
Accessories	
International power supply adapter (UK, EU, AU):	C4-TSIPS International Portable includes both Power adapters: C4-TSMC7-INT
7" Portable Touch Screen with Camera Dock	C4-TSMC7-DOCK
Intercom License	C4-Intercom-E

Also available are the Control4® 5" and 7" In-Wall Touch Screens (Audio Intercom-capable only). For a complete list of Intercom compatibilities, please refer to the Intercom License datasheet.

For product photos, documentation and installation instructions, visit:
<http://www.control4.com/dealer/products/interfaces>

